

1

2

3

4

D

C

B


A

BREAK SHARP CORNERS MAY BE EITHER CHAMFER OR RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.

THIS DRAWING IS A SOLE PROPERTY OF M & M I t d. IT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THEIR CONSENT

REFER DRAWING : — 007537394C91

REF PART NO: 007537394C91

UNSPECIFIED TOLERANCES FOR PART		SURFACE FINISH SYMBOLS:ISO-1302				MAHINDRA & MAHINDRA LTD. FARM DIVISION, INDIA		
FORMING TO FORMING	UPTO 500 ±0.5 ABOVE 500 ±0.8	WELDING SYMBOLS:IS813 REMOVE ALL SHARP CORNERS & BURRS						
CD BETWEEN HOLES	IN ONE PLANE ±0.2 IN DIFF PLANES±0.5	DO NOT SCALE ALL DIMENSIONS ARE IN mm	<SC> COUNT : 0	NAME	DATE	PROJECT CODE:		
FORM TO PIERCE	±0.5		<CC> COUNT : 0	DSNR	AR	07-06-2023	ER NUMBER: ER23C00000228	
HOLE SIZES	+0.2/-0		WEIGHT(kg) : 0.15	CHKR	NVC	07-06-2023	DESCRIPTION :	
SLOT SIZES	±0.8		S/F AREA(cm²): 66	APPR	DS	07-06-2023	PLATE CLUTCH SPRING MTG	
FLANGE WIDTH	+1.0/-0.7		MATERIAL:		PART NUMBER :		CL:	
JOGGLE DEPTH	+0.3/0				008032665U01		NA	
UNSPECIFIED TOLERANCES FOR PART & ASSEMBLY					DWG.SIZE : A4		SCALE : 1:1	SHEET: 1 OF 1
GENERAL TOLERANCES	UP TO 300 ±0.8 ABOVE 300 ±1.0							
ANGULAR TOLERANCE	±1°							

CHECK DRAWING WITH LATEST CHANGE No

DO NOT CHANGE MANUALLY

COMPUTER GENERATED DRAWING

4